CARMIX TRAILER PUMP 15

2-cylinder piston pumps, hydraulic driven
Ideal for pumping up to 15 m³/h
COMPLETE WITH AUTOMATIC GREASING SYSTEM

Max pumping Height: 60-70 m
Max pumping distance: 80-90 m

- Yanmar 31HP 3 Cylinders liquid cooled diesel engine
- Concrete hopper with agitator
- Grid with 12V vibrator
- Pumping unit with S-Tilting valve for automatic compensation of clearance and wear
- EasySpritz system: best pumping performance also at low flow rate
- 4″ Victaulic delivery manifold (= 100 mm)
- Control panel with electromechanical devices
- 4-Function wire remote control
- Road-towable unit complete with parking brake and lights
- Compact and easy to move
- Dimensions: w/l/h: 1495/4100/1540 mm
- Weight: 1550 kg

CARMIX®
4x4 mixers & dumpers

- **2 CYLINDERS PISTON PUMP, HYDRAULIC DRIVE**
- **Flow rate upto 15 m³/h**
- **Max aggregate size 25 mm**
- **Pumping pressure 70 bar**
- **Hopper capacity 240 liters**

ACCESSORIES ON DEMAND

STOWABLE CE KIT

CONCRETE PUMPING KIT:
07 Steel pipes dn 4" L 3 mt for Victaulic 4"
01 Rubber hose 4" L 3 mt for Victaulic 4"
01 Steel bends dn 4" r=250/90° Victaulic
02 Steel bends dn 4" r=250/45° Victaulic
12 Victaulic coupling dn 4"
15 Gasket for Victaulic coupling dn 4"
02 Cleaning ball dor hose diam. 150/200
01 Basket for cleaning ball recovery dn 4"
01 90° bend with ball inlet port
01 Bend top 100 Victaulic

SHOTCRETING SPRITZBETON KIT:
02 rubber hose dn 50 mm , l. 10 m Victaulic 2" – Victaulic 2"
01 rubber hose dn 50 mm , l. 10 m Victaulic 2" – cam dn 50
01 complete hopper gun dn 50 with fast Geka coupling ¾ " for air
01 reduction cone dn 100 (4")-dn 50 (2")Victualic l = 1000 m
01 hanging belt for hose
02 cleaning ball for hose dn. 50
01 Victualic coupling dn 4"
02 gasket for Victualic coupling dn 4"
03 Victualic coupling dn 2"
06 gasket for Victualic coupling dn 2"
01 gasket for cam coupling dn 50