

CARMIX TRAILER PUMP 15

2-cylinder piston pumps, hydraulic driven
Ideal for pumping up to 15 m³/h
Complete with Automatic Greasing System

Max pumping Height: 60-70 m
Max pumping distance: 80-90 m

- Yanmar 31HP 3 Cylinders liquid cooled diesel engine
- Concrete hopper with agitator
- Grid with 12V vibrator
- Pumping unit with S-Tilting valve for automatic compensation of clearance and wear
- EasySpritz system: best pumping performance also at low flow rate
- 4" Victaulic delivery manifold (= 100 mm)
- Control panel with electromechanical devices
- 4-Function wire remote control
- Road-towable unit complete with parking brake and lights
- Compact and easy to move
- Dimensions: w/l/h: 1495/4100/1540 mm
- Weight: 1550 kg



- + **2 CYLINDERS PISTON PUMP, HYDRAULIC DRIVE**
- + **Flow rate upto 15 m³/h**
- + **Max aggregate size 25 mm**
- + **Pumping pressure 70 bar**
- + **Hopper capacity 240 liters**

ACCESSORIES ON DEMAND

STOWABLE CE KIT

CONCRETE PUMPING KIT:

- 07 Steel pipes dn 4" L 3 mt for Victaulic 4"
- 01 Rubber hose 4" L 3 mt for Victaulic 4"
- 01 Steel bends dn 4" r=250/90° Victaulic
- 02 Steel bends dn 4" r=250/45° Victaulic
- 12 Victaulic coupling dn 4"
- 15 Gasket for Victaulic coupling dn 4"
- 02 Cleaning ball dor hose diam. 150/200
- 01 Basket for cleaning ball recovery dn 4"
- 01 90° bend with ball inlet port
- 01 Bend top 100 Victaulic

SHOTCRETING SPRITZBETON KIT:

- 02 rubber hose dn 50 mm , l. 10 m Victualic 2" - Victualic 2"
- 01 rubber hose dn 50 mm , l. 10 m Victualic 2" - cam dn 50
- 01 complete hopper gun dn 50 with fast Geka coupling 3/4" for air
- 01 reduction cone dn 100 (4")-dn 50 (2")Victualic l = 1000 m
- 01 hanging belt for hose
- 02 cleaning ball for hose dn. 50
- 01 Victualic coupling dn 4"
- 02 gasket for Victualic coupling dn 4"
- 03 Victualic coupling dn 2"
- 06 gasket for Victualic coupling dn 2"
- 01 gasket for cam coupling dn 50